



## SECTION 1: DESCRIPTION & BENEFITS

- Material: PP-Polypropylene, high transparency
- PP backing with high tensile strength & high tenacity
- Environment friendly material, long life span
- Customized width and length, as well as colors.
- Water and moisture resistance
- Imported high quality PP material provides strong holding
- High precision emboss, offers excellent slip resistance
- Smooth clean edges protect your hand



## SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Color	White Transparent	Visual
Total Thickness	0.6 mm (24 mil)	PSTC-133/ASTM D3652
Width	12 mm	Gauges
Length	2900 m	Measure
Weight	10 kgs	Weigh
Tensile Strength	> 1000 N	PSTC-131/ASTM D3759
Elongation at Break	≥ 20%	PSTC-131/ASTM D3759

## SECTION 3: APPLICATIONS & OTHER DETAILS

- Used for refrigerator packing
- To combine, stabilize, hold, reinforce, or fasten an item

**Standard width:** 9 mm, 11mm, 12mm, 15mm, 18mm; **Standard length:** 1200m, 1500m, 2000m, 2500, 2900m, etc.

**Tolerance:** Thickness: +/- 10%      Width: +/-1.0mm      Length: +/- 0.8m

**Storage:** Indoor storage: 10°C-28°C, humidity: <80%, cool & dry, free of direct sunlight

**Shelf Life:** 6 months in room temp. We recommend you use out in 3 months, to reach best condition of tape.

**\*N.B.** Performance data above are conducted in Egret lab, based on PSTC/ASTM methods. It can only be treated as a reference; we don't guarantee the accuracy. Individual rolls might vary from these data, due to different environment, test methods, equipment. The choice of tape is the responsibility of the buyer.

The tape should be applied on a clean & dry surface. Egret tape mustn't be exposed direct to the sunlight when applied or stored. Egret reserve the right to modify tape data without notice.

**Changzhou Egret Manufacturing Co., Ltd**

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807      Email: info@egretmfg.com      Website: www.egretmfg.com